

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830

BENZY
MARKENPRODUKTE

Article No.: 34501001
Print date: 11.07.2022
Version: 1.0

Empire Dirt Blocker
Revision date: 22.04.2022
Issue date: 14.03.2022

EN
Page 1 / 9

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. **product identifiers**

Article No. (manufacturer/supplier) 34501001
Trade name/designation Empire Dirt Blocker
For Sneakers & Caps
UFI: QUF8-WEDR-163Q-6S4W

1.2. **Relevant identified uses of the substance or mixture and uses advised against**

Relevant identified uses:

Textile impregnator

1.3. **Details of the supplier of the safety data sheet**

supplier (manufacturer/importer/downstream user/distributor)

Benzy Markenprodukte GmbH
Zum Schacht 3 Telephone: +49 - (0)6825 / 89698 - 0
D-66287 Götterborn Telefax: +49 - (0)6825 / 89698 - 40
E-mail info@benzy-gmbh.de

Department responsible for information:

E-mail (competent person) info@benzy-gmbh.de

1.4. **Emergency telephone number**

111 (England, Wales, Scotland)

SECTION 2: Hazards identification

2.1. **Classification of the substance or mixture**

Classification according to Regulation (EC) No 1272/2008 [CLP]

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

Aerosol 1 / H222	Aerosol	Extremely flammable aerosol.
Aerosol 1 / H229	Aerosol	Pressurised container: May burst if heated.
Eye Irrit. 2 / H319	Serious eye damage/eye irritation	Causes serious eye irritation.
STOT SE 3 / H336	STOT-single exposure	May cause drowsiness or dizziness.

2.2. **Label elements**

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms



Danger

Hazard statements

H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P103 Read carefully and follow all instructions.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P260 Do not breathe aerosol.
P271 Use only outdoors or in a well-ventilated area.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313 If eye irritation persists: Get medical advice/attention.
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501 Inhalt/Behälter entsprechend den örtlichen Vorschriften der Entsorgung zuführen.

Hazard components for labelling

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830

BENZY
MARKENPRODUKTE

Article No.: 34501001
Print date: 11.07.2022
Version: 1.0

Empire Dirt Blocker
Revision date: 22.04.2022
Issue date: 14.03.2022

EN
Page 2 / 9

propane-2-ol

Supplemental hazard information

not applicable

2.3. Other hazards

No information available.

Caution! Important note! Inhalation may be damaging to health. Use only outdoors or in a well ventilated area! Spray for just a few seconds! Spray larger leather products or textiles outdoors only and allow to air-dry thoroughly! Keep out of reach of children.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Description Alcoholic mixture with special additives

Classification according to Regulation (EC) No 1272/2008 [CLP]

EC No. CAS No. Index No.	REACH No. Designation classification // Remark	weight-%
200-661-7 67-63-0	01-2119457558-25 propane-2-ol	50 - 70
603-117-00-0	Flam. Liq. 2 H225 / Eye Irrit. 2 H319 / STOT SE 3 H336	
203-448-7 106-97-8	01-2119474691-32 butane	20 - 25
601-004-00-0	compressed gas H280 / Flam. Gas 1 H220	
204-658-1 123-86-4	01-2119485493-29 n-butyl acetate	10 - 15
607-025-00-1	Flam. Liq. 3 H226 / STOT SE 3 H336	
200-827-9 74-98-6	01-2119486944-21 propane	5 - 10
601-003-00-5	compressed gas H280 / Flam. Gas 1 H220	
200-857-2 75-28-5	01-2119485395-27 isobutane	1 - 2,5
601-004-00-0	compressed gas H280 / Flam. Gas 1 H220	

Additional information

Full text of classification: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

Following ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

Article No.: 34501001
Print date: 11.07.2022
Version: 1.0

Empire Dirt Blocker
Revision date: 22.04.2022
Issue date: 14.03.2022

EN
Page 3 / 9

5.1. Extinguishing media

Suitable extinguishing media

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

Unsuitable extinguishing media

strong water jet

5.2. Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

5.3. Advice for firefighters

Provide a conveniently located respiratory protective device. Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

6.3. Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Clean using cleansing agents. Do not use solvents.

6.4. Reference to other sections

Observe protective provisions (see section 7 and 8).

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advices on safe handling

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Electrical equipment must be protected meeting the accepted standard. Product may become electrostatically charged. Provide earthing of containers, equipment, pumps and ventilation facilities. Anti-static clothing including shoes are recommended. Floors must be electrically conductive. Keep away from heat sources, sparks and open flames. Use only spark proof tools. Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. Avoid respiration of swarf. When using do not eat, drink or smoke. Personal protection equipment: refer to section 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

Further information

Vapours are heavier than air. Vapours form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (TRGS 727)".

Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

Further information on storage conditions

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 15 °C and 30 °C. Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

7.3. Specific end use(s)

Observe technical data sheet. Observe instructions for use.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Article No.: 34501001
Print date: 11.07.2022
Version: 1.0

Empire Dirt Blocker
Revision date: 22.04.2022
Issue date: 14.03.2022

EN
Page 4 / 9

Occupational exposure limit values:

propane-2-ol
Index No. 603-117-00-0 / EC No. 200-661-7 / CAS No. 67-63-0

WEL, TWA: 999 mg/m³; 400 ppm
WEL, STEL: 1250 mg/m³; 500 ppm

butane
Index No. 601-004-00-0 / EC No. 203-448-7 / CAS No. 106-97-8

WEL, TWA: 1450 mg/m³; 600 ppm
WEL, STEL: 1810 mg/m³; 750 ppm

Additional information

TWA : Long-term occupational exposure limit value
STEL : short-term occupational exposure limit value
Ceiling : peak limitation

8.2. **Exposure controls**

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

Personal protection equipment

Respiratory protection

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Use only respiratory protection equipment with CE-symbol including four digit test number.

Hand protection

For prolonged or repeated handling the following glove material must be used: nitrile rubber or butyl rubber with at least 0.7 mm thickness

Thickness of the glove material > 0,4 mm ; Breakthrough time: > 480 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles EN ISO 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Eye/face protection

Wear closely fitting protective glasses in case of splashes.

Body protection

Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

Protective measures

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

Environmental exposure controls

Do not allow to enter into surface water or drains. See section 7. No additional measures necessary.

SECTION 9: Physical and chemical properties

9.1. **Information on basic physical and chemical properties**

Appearance:

Physical state: Liquid
Colour: clear

Odour: like organic solvents

Odour threshold: not determined

pH at 20 °C: not applicable
Method: DIN 19268

Melting point/freezing point: not determined

Initial boiling point and boiling range: -11 °C
Source: isobutane

Flash point: -60 °C
Method: DIN 51755 part 1

Evaporation rate: not determined
flammability

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830

BENZY
MARKENPRODUKTE

Article No.: 34501001
Print date: 11.07.2022
Version: 1.0

Empire Dirt Blocker
Revision date: 22.04.2022
Issue date: 14.03.2022

EN
Page 5 / 9

Burning time:	not determined
Upper/lower flammability or explosive limits:	
Lower explosion limit:	1,2 Vol-% Source: n-butyl acetate
Upper explosion limit:	13 Vol-% Source: propane-2-ol
Vapour pressure at 20 °C:	979,5295 mbar
Vapour density:	not determined
Relative density:	
Density at 20 °C:	0,73 g/cm³ Method: DIN EN ISO 15212-1
Solubility(ies):	
Water solubility at 20 °C:	insoluble
Partition coefficient: n-octanol/water:	see section 12
Auto-ignition temperature:	365 °C Source: butane
Decomposition temperature:	not determined
Viscosity at 20 °C:	< 10 mPa*s Method: DIN 53019
Explosive properties:	not determined
Oxidising properties:	not determined
9.2. Other information	
Solid content:	1,28 weight-%
solvent content:	
Organic solvents:	99 weight-%
Water:	0 weight-%
Solvent separation test:	< 3 weight-% (ADR/RID)

SECTION 10: Stability and reactivity

- 10.1. **Reactivity**
No information available.
- 10.2. **Chemical stability**
Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7.
- 10.3. **Possibility of hazardous reactions**
Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.
- 10.4. **Conditions to avoid**
Hazardous decomposition byproducts may form with exposure to high temperatures.
- 10.5. **Incompatible materials**
not applicable
- 10.6. **Hazardous decomposition products**
Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

SECTION 11: Toxicological information

Classification according to Regulation (EC) No 1272/2008 [CLP]

11.1. Information on toxicological effects

Acute toxicity

n-butyl acetate
oral, LD50, Rat: 10760 mg/kg
Method: OECD 423
dermal, LD50, Rabbit: > 14112 mg/kg
Method: OECD 402
inhalative (Gases), LC50, Rat: 23,4 ppmV (4 h)

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830

BENZY
MARKENPRODUKTE

Article No.: 34501001
Print date: 11.07.2022
Version: 1.0

Empire Dirt Blocker
Revision date: 22.04.2022
Issue date: 14.03.2022

EN
Page 6 / 9

Method: OECD 403

propane-2-ol

oral, LD50, Rat: 5840 mg/kg

Method: OECD 401

dermal, LD50, Rabbit: 13900 mg/kg

Method: OECD 402

inhalative (vapours), LC50, Rat: > 25 mg/L (6 h)

Method: OECD 403

Skin corrosion/irritation; Serious eye damage/eye irritation

Causes serious eye irritation.

n-butyl acetate

Skin, Rabbit

Method: OECD 404

eyes

Method: OECD 405

propane-2-ol

Skin

Method: OECD 404

Prolonged/repetitive skin contact may cause skin defatting or dermatitis.

eyes

Method: OECD 405

Liquid splashes can lead to irritations of the eyes.

Respiratory or skin sensitisation

n-butyl acetate

Skin, Guinea pig: ; Evaluation not sensitising.

Method: OECD 406

propane-2-ol

Skin, Regulation (EC) No. 440/2008, Annex B.6 (Bühler test), Guinea pig: ; Evaluation not sensitising.

Method: OECD 406

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Based on available data, the classification criteria are not met.

STOT-single exposure; STOT-repeated exposure

May cause drowsiness or dizziness.

propane-2-ol

Specific target organ toxicity (single exposure), drowsiness Evaluation May cause drowsiness or dizziness.

Aspiration hazard

Based on available data, the classification criteria are not met.

Practical experience/human evidence

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: headache, dizziness, fatigue, amyosthenia, drowsiness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

Overall Assessment on CMR properties

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

SECTION 12: Ecological information

Classification according to Regulation (EC) No 1272/2008 [CLP]

Do not allow to enter into surface water or drains.

12.1. Toxicity

n-butyl acetate

Fish toxicity, LC50, Pimephales promelas (fathead minnow): 18 mg/L (96 h)

Method: OECD 203

Daphnia toxicity, EC50, Daphnia magna (Big water flea): 44 mg/L (48 h)

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830

BENZY
MARKENPRODUKTE

Article No.: 34501001
Print date: 11.07.2022
Version: 1.0

Empire Dirt Blocker
Revision date: 22.04.2022
Issue date: 14.03.2022

EN
Page 7 / 9

Algae toxicity, ErC50, *Desmodesmus subspicatus*: 647,7 mg/L (72 h)
propane-2-ol
Fish toxicity, LC50, *Pimephales promelas*: 9640 mg/L (96 h)
Method: OECD 203
Daphnia toxicity, LC50, *Daphnia magna* (Big water flea): 9714 mg/L (24 h)
Method: OECD 202
, EC50, *Scenedesmus subspicatus*: > 100 mg/L (72 h)
Bacteria toxicity: > 100 mg/L
Algae toxicity, LOEC, Algae: 1000 mg/L (8 d)

Long-term Ecotoxicity

n-butyl acetate
Algae toxicity, NOEC, *Desmodesmus subspicatus*: 200 mg/L
Inhibition of growth rate.
Bacterial toxicity, IC50, *Tetrahymena*: 356 mg/L (40 h)

12.2. Persistence and degradability

n-butyl acetate
Biodegradation, aerobic: 83 % (28 D); Evaluation Readily biodegradable (according to OECD criteria).
Method: OECD 301D/ EEC 92/69/V, C.4-E
propane-2-ol
Biodegradation, Aerobic biological treatment: 53 % (5 d); Evaluation Readily biodegradable (according to OECD criteria).

12.3. Bioaccumulative potential

n-butyl acetate
Partition coefficient: n-octanol/water: 2,3
Method: OECD 117
Surface tension, 1 g/l; 20°C: 61,3 mN/m
Method: OECD 115

propane-2-ol
Partition coefficient: n-octanol/water: 0,05

12.4. Mobility in soil

Toxicological data are not available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Appropriate disposal / Product Recommendation

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

List of proposed waste codes/waste designations in accordance with EWC

150110* packaging containing residues of or contaminated by dangerous substances

*Hazardous waste according to Directive 2008/98/EC (waste framework directive).

Appropriate disposal / Package Recommendation

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

SECTION 14: Transport information

14.1. UN number

UN 1950

14.2. UN proper shipping name

Land transport (ADR/RID): DRUCKGASPACKUNGEN, entzündbar

Sea transport (IMDG): AEROSOLS

Air transport (ICAO-TI / IATA-DGR): Aerosols, flammable

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830

BENZY
MARKENPRODUKTE

Article No.: 34501001
Print date: 11.07.2022
Version: 1.0

Empire Dirt Blocker
Revision date: 22.04.2022
Issue date: 14.03.2022

EN
Page 8 / 9

14.3. Transport hazard class(es)

2.1

14.4. Packing group

not applicable

14.5. Environmental hazards

Land transport (ADR/RID)

not applicable

Marine pollutant

not applicable

14.6. Special precautions for user

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.

Advices on safe handling: see parts 6 - 8

Further information

Land transport (ADR/RID)

tunnel restriction code

D

Sea transport (IMDG)

EmS-No.

F-D, S-U

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Directive 2010/75/EU on industrial emissions [Industrial Emissions Directive]

VOC-value (in g/L): 720,876

National regulations

Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

15.2. Chemical Safety Assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

EC No. CAS No.	Designation	REACH No.
200-661-7 67-63-0	propane-2-ol	01-2119457558-25
204-658-1 123-86-4	n-butyl acetate	01-2119485493-29

SECTION 16: Other information

Full text of classification in section 3

Flam. Liq. 2 / H225

Flammable liquids

Highly flammable liquid and vapour.

Eye Irrit. 2 / H319

Serious eye damage/eye irritation

Causes serious eye irritation.

STOT SE 3 / H336

STOT-single exposure

May cause drowsiness or dizziness.

compressed gas / H280

Gases under pressure

Contains gas under pressure; may explode if heated.

Flam. Gas 1 / H220

flammable gases

Extremely flammable gas.

Flam. Liq. 3 / H226

Flammable liquids

Flammable liquid and vapour.

Classification procedure

Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Aerosol 1

Aerosol

On basis of test data.

Aerosol 1

Aerosol

On basis of test data.

Eye Irrit. 2

Serious eye damage/eye irritation

Calculation method.

STOT SE 3

STOT-single exposure

Calculation method.

Abbreviations and acronyms

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830

BENZY
MARKENPRODUKTE

Article No.: 34501001
Print date: 11.07.2022
Version: 1.0

Empire Dirt Blocker
Revision date: 22.04.2022
Issue date: 14.03.2022

EN
Page 9 / 9

ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
OEL	Occupational Exposure Limit Value
BLV	Biological Limit Value
CAS	Chemical Abstracts Service
CLP	Classification, Labelling and Packaging
CMR	Carcinogenic, Mutagenic and Reprotoxic
DIN	German Institute for Standardization / German industrial standard
DNEL	Derived No-Effect Level
EAKV	European Waste Catalogue Directive
EC	Effective Concentration
EC	European Community
EN	European Standard
IATA-DGR	International Air Transport Association – Dangerous Goods Regulations
IBC Code	International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
ICAO-TI	International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous Goods by Air
IMDG Code	International Maritime Code for Dangerous Goods
ISO	International Organization for Standardization
LC	Lethal Concentration
LD	Lethal Dose
MARPOL	Maritime Pollution: The International Convention for the Prevention of Pollution from Ships
OECD	Organisation for Economic Cooperation and Development
PBT	persistent, bioaccumulative, toxic
PNEC	Predicted No Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
UN	United Nations
VOC	Volatile Organic Compounds
vPvB	very persistent and very bioaccumulative

Further information

Classification according to Regulation (EC) No 1272/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in section 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.